

# TRANSPORT FOR NSW (TfNSW)

## SPECIFICATION D&C 3263

### HOT POURED ELASTOMERIC JOINT SEALANT FOR ROADS

#### NOTICE

This document is a Transport for NSW D&C Specification. It has been developed for use with Design & Construct roadworks and bridgeworks contracts let by Transport for NSW. It is not suitable for any other purpose and must not be used for any other purpose or in any other context.

Copyright in this document belongs to Transport for NSW.

#### REVISION REGISTER

<b>Ed/Rev Number</b>	<b>Clause Number</b>	<b>Description of Revision</b>	<b>Authorised By</b>	<b>Date</b>
Ed 1/Rev 0		First issue	GM, CPS	10.10.13
Ed 1/Rev 1	Global	References to “Roads and Maritime Services” or “RMS” changed to “Transport for NSW” or “TfNSW” respectively. References to “RMS Representative” changed to “Principal”.	DCS	22.06.20





Transport  
for NSW

SPECIFICATION D&C 3263

---

# HOT Poured ELASTOMERIC JOINT SEALANT FOR ROADS

Copyright – Transport for NSW  
IC-DC-3263

VERSION FOR: DATE:
-----------------------



**CONTENTS**

<b>CLAUSE</b>	<b>PAGE</b>
FOREWORD .....	ii
TfNSW Copyright and Use of this Document.....	ii
Base Specification .....	ii
1    SCOPE .....	1
2    STRUCTURE OF THE SPECIFICATION.....	1
2.1    (Not Used) .....	1
2.2    Schedule of Identified Records .....	1
2.3    (Not Used) .....	1
2.4    Referenced Documents and Definitions.....	1
3    SUPPLIER’S QUALITY MANAGEMENT SYSTEM.....	1
4    MATERIAL REQUIREMENTS.....	2
4.1    Safety.....	2
4.2    Physical Properties.....	2
5    PRODUCT CERTIFICATION.....	2
6    DETAILS OF CONSIGNMENT .....	2
ANNEXURES 3263/A TO 3263/B – (NOT USED).....	4
ANNEXURE 3263/C – SCHEDULE OF IDENTIFIED RECORDS .....	4
ANNEXURES 3263/D TO 3263/L – (NOT USED) .....	4
ANNEXURE 3263/M – REFERENCED DOCUMENTS.....	4
LAST PAGE OF THIS DOCUMENT IS .....	4

## **FOREWORD**

### **TfNSW COPYRIGHT AND USE OF THIS DOCUMENT**

Copyright in this document belongs to Transport for NSW.

#### **When this document forms part of a deed**

This document should be read with all the documents forming the Project Deed.

#### **When this document does not form part of a deed**

This copy is not a controlled document. Observe the Notice that appears on the first page of the copy controlled by TfNSW. A full copy of the latest version of the document is available on the TfNSW Internet website: <http://www.rms.nsw.gov.au/business-industry/partners-suppliers/specifications/index.html>

### **BASE SPECIFICATION**

This document is based on Specification TfNSW 3263 Edition 3 Revision 1.

# TfNSW QA SPECIFICATION D&C 3263

## HOT POURED ELASTOMERIC JOINT SEALANT FOR ROADS

### 1 SCOPE

This Specification sets out the requirements for hot poured elastic joint sealants for use in concrete and asphalt pavements to guard against the penetration of water and foreign matter.

Note 1 Hot poured joint sealants which meet the requirements of this Specification may require the use of a primer on concrete surfaces.

### 2 STRUCTURE OF THE SPECIFICATION

This Specification includes a series of annexures that detail additional requirements.

#### 2.1 (NOT USED)

#### 2.2 SCHEDULE OF IDENTIFIED RECORDS

The records listed in Annexure 3263/C are **Identified Records** for the purposes of Specification TfNSW D&C Q6 Annexure Q/E.

#### 2.3 (NOT USED)

#### 2.4 REFERENCED DOCUMENTS AND DEFINITIONS

Standards, specifications and test methods are referred to in abbreviated form (e.g. AS2439.1). For convenience, the full titles are given in Annexure 3263/M.

The term “the Supplier” means the supplier of the product covered by the scope of this Specification.

### 3 SUPPLIER’S QUALITY MANAGEMENT SYSTEM

The Supplier must establish and maintain a Quality Management System complying with AS/NZS ISO 9001 as a means of ensuring that the product conforms to this Specification.

Provide evidence verifying compliance with this Clause.

## 4 MATERIAL REQUIREMENTS

### 4.1 SAFETY

The material must contain no known compound which, when handled according to approved road making practice and within the temperature range recommended by the manufacturer, will cause any worker to be exposed to any injurious substance above the legal limit concentration. A Safety Data Sheet will be supplied.

### 4.2 PHYSICAL PROPERTIES

Joint sealing materials must meet the requirements set out in Table 3263.1.

**Table 3263.1 Properties of Hot Poured Joint Sealants**

Test Reference	Test Description	Unit	Requirement
TfNSW T1171	Flow test	%	10 (maximum)
TfNSW T1179	Penetration	mm	13.0 (maximum)
ASTM D3407*;	Resilience	%	60 (minimum)
Section 8	Initial Indentation (P)	mm	$0.5 \leq P \leq 2.0$
TfNSW T1172	Tensile Bond Strength		
	Adhesion	mm <sup>2</sup>	250 max
	Cohesion (ruptures)	mm <sup>2</sup>	40 max
	(cavity)	mm	6 max
TfNSW T1173	Heat Degradation	%	As TfNSW T1171 & TfNSW T1172 above
TfNSW T1181	Extensibility	%	500 (minimum)

\* TfNSW T1170 must be used for sample preparation

## 5 PRODUCT CERTIFICATION

Provide a certificate of conformity verifying that the joint sealing material complies with Table 3263.1, together with test results reported on approved endorsed test documents.

The certificate must relate only to the formulation on which the tests were carried out and must be valid for not more than three years. New certification will be required whenever a change in product formulation is made.

## 6 DETAILS OF CONSIGNMENT

Mark each container clearly and durably with the following information:

- (i) The name of the supplier;



- (ii) The trade name of the product;
- (iii) Product reference and identification number;
- (iv) Batch number or date of manufacture.

Provide a copy of the certificate of compliance and a Safety Data Sheet with each delivery.

## **ANNEXURES 3263/A TO 3263/B – (NOT USED)**

## **ANNEXURE 3263/C – SCHEDULE OF IDENTIFIED RECORDS**

Refer to Clause 2.2.

The records listed below are Identified Records for the purposes of TfNSW D&C Q6 Annexure Q/E.

<b>Clause</b>	<b>Description of Identified Record</b>
5	Certificate of conformity verifying that the joint sealing material complies with this Specification, together with tests results reported on NATA endorsed test documents
6	Certificate of conformity, Materials Safety Data Sheet and Materials Data Sheet to be supplied with each delivery

## **ANNEXURES 3263/D TO 3263/L – (NOT USED)**

## **ANNEXURE 3263/M – REFERENCED DOCUMENTS**

Refer to Clause 2.4.

### **TfNSW Specification**

TfNSW D&C Q6      Quality Management System (Type 6)

### **TfNSW Test Methods**

TfNSW T1170      Preparation of Hot Poured Joint Sealing Compound for Test  
TfNSW T1171      Flow Properties of Hot Poured Joint Sealant  
TfNSW T1172      Tensile Bond Strength for Hot Poured Joint Sealant  
TfNSW T1173      Heat Degradation Test on Hot Poured Joint Sealing Compound  
TfNSW T1179      Penetration into Joint Sealant  
TfNSW T1181      Extension Test for Hot Poured Joint Sealant

### **Australian Standard**

AS/NZS ISO 9001      Quality management systems - Requirements

### **ASTM Standard**

ASTM D3407      Standard Methods of Testing Joint Sealants, Hot Poured, for Concrete and Asphalt Pavements