

TRANSPORT FOR NSW (TfNSW)

SPECIFICATION D&C 3268

AGGREGATE PRECOATING AGENT (FOR POLYMER MODIFIED BINDER)

NOTICE

This document is a Transport for NSW D&C Specification. It has been developed for use with Design & Construct roadworks and bridgeworks contracts let by Transport for NSW. It is not suitable for any other purpose and must not be used for any other purpose or in any other context.

Copyright in this document belongs to Transport for NSW.

REVISION REGISTER

Ed/Rev Number	Clause Number	Description of Revision	Authorised By	Date
Ed 1/Rev 0		First issue	GM, IC W Stalder	01.07.11
Ed 1/Rev 1	Global	References to “Roads and Maritime Services” or “RMS” changed to “Transport for NSW” or “TfNSW” respectively. References to “RMS Representative” changed to “Principal”.	DCS	22.06.20



Transport
for NSW

SPECIFICATION D&C 3268

AGGREGATE PRECOATING AGENT (FOR POLYMER MODIFIED BINDER)

Copyright – Transport for NSW
IC-DC-3268

VERSION FOR: DATE:

CONTENTS

CLAUSE	PAGE
FOREWORD	ii
TfNSW Copyright and Use of this Document.....	ii
Base Specification	ii
1 SCOPE	1
2 STRUCTURE OF THE SPECIFICATION.....	1
2.1 (Not Used)	1
2.2 Schedule of Identified Records	1
2.3 (Not Used)	1
2.4 Referenced Documents and Definitions.....	1
3 (NOT USED).....	1
4 SUPPLIER’S QUALITY MANAGEMENT SYSTEM.....	1
5 MATERIAL REQUIREMENTS.....	2
5.1 General	2
5.2 Safety.....	2
5.3 Homogeneity of Liquid Precoat	2
5.4 Initial Adhesion.....	2
5.5 Resistance to Stripping.....	2
5.6 Keeping Qualities	2
5.7 Concentration of Active Component	3
6 PRODUCT CERTIFICATION.....	3
7 IDENTIFICATION OF CONTAINERS	3
8 INFORMATION TO BE PROVIDED BY SUPPLIER.....	3
ANNEXURES 3268/A TO 3268/B – (NOT USED)	4
ANNEXURE 3268/C – SCHEDULE OF IDENTIFIED RECORDS	4
ANNEXURES 3268/D TO 3268/L – (NOT USED)	5
ANNEXURE 3268/M – REFERENCED DOCUMENTS.....	5
LAST PAGE OF THIS DOCUMENT IS	5

FOREWORD

TfNSW COPYRIGHT AND USE OF THIS DOCUMENT

Copyright in this document belongs to Transport for NSW.

When this document forms part of a deed

This document should be read with all the documents forming the Project Deed.

When this document does not form part of a deed

This copy is not a controlled document. Observe the Notice that appears on the first page of the copy controlled by TfNSW. A full copy of the latest version of the document is available on the TfNSW Internet website: <http://www.rms.nsw.gov.au/business-industry/partners-suppliers/specifications/index.html>

BASE SPECIFICATION

This document is based on Specification TfNSW 3268 Edition 5 Revision 1.

TfNSW SPECIFICATION D&C 3268

AGGREGATE PRECOATING AGENT (FOR POLYMER MODIFIED BINDER)

1 SCOPE

This Specification sets out the requirements for precoating agents for aggregate used in spray sealing with various grades of polymer modified binder. Precoating agents may be either ready for use or in a concentrated form to be blended before use.

2 STRUCTURE OF THE SPECIFICATION

This Specification includes a series of annexures that detail additional requirements.

2.1 (NOT USED)

2.2 SCHEDULE OF IDENTIFIED RECORDS

The records listed in Annexure 3268/C are **Identified Records** for the purposes of Specification TfNSW D&C Q6 Annexure Q/E.

2.3 (NOT USED)

2.4 REFERENCED DOCUMENTS AND DEFINITIONS

Standards, specifications and test methods are referred to in abbreviated form (e.g. AS 2350). For convenience, the full titles are given in Annexure 3268/M.

The term “the Supplier” means the supplier of the product covered by the scope of this Specification.

3 (NOT USED)

4 SUPPLIER’S QUALITY MANAGEMENT SYSTEM

The Supplier must establish and maintain a Quality Management System complying with AS/NZS ISO 9001 as a means of ensuring that the product conforms to this Specification.

Provide evidence verifying compliance with this Clause.

5 MATERIAL REQUIREMENTS

5.1 GENERAL

Ready for use precoating agents must be cutback bitumen grade AMC00 complying with AS 2157 or other proprietary materials.

5.2 SAFETY

The material must not contain any components which, when handled in accordance with approved work practices (such as those contained in “TfNSW Sprayed Sealing Guide” and “Austroads Guide to Pavement Technology Part 4B”), will cause the worker to be exposed to harmful substances above the legal limit concentration.

5.3 HOMOGENEITY OF LIQUID PRECOAT

The precoating agent after agitation and when ready for use must be homogeneous and remain free from skinning precipitation or any other deterioration for 72 hours (Test Method TfNSW T590).

5.4 INITIAL ADHESION

When tested in accordance with Test Method TfNSW T238 with the specified grade of polymer modified binder and each of the four aggregates: Microgranite (ex Mugga 1 Quarry, Canberra), Basalt (ex Peats Ridge), Quartzite (ex Marrangaroo, Lithgow) and Nepean River Gravel (ex Emu Plains) under the following four surface conditions:

- (i) clean and dry;
- (ii) dusty;
- (iii) saturated surface dry;
- (iv) saturated surface wet,

the percentage stripped must not exceed 10% with any combination of aggregate and surface condition listed above.

5.5 RESISTANCE TO STRIPPING

When tested in accordance with Test Method TfNSW T230 with the specified grade of polymer modified binder and the four aggregates under the four surface conditions stated in Clause 5.4, the percentage stripped must not exceed 10% for any combination of aggregate and surface condition listed in Clause 5.3.

5.6 KEEPING QUALITIES

The precoating agent must be able to comply with Clauses 5.3 to 5.5 after storage in the temperature range 4°C to 40°C in unopened containers for 6 months from the date of despatch by the Supplier.

5.7 CONCENTRATION OF ACTIVE COMPONENT

Provide details of a reproducible laboratory test which will allow the concentration of the active component of the material to be determined. Specify an average value for the concentration of the active component and an acceptable minimum value above which the material is considered to be effective.

6 PRODUCT CERTIFICATION

Provide a certificate of compliance verifying that the precoating agent complies with Clause 5 of this Specification, together with test results reported on NATA endorsed test documents.

The certification must relate only to the formulation of the product on which the tests were carried out. New certification will be required every three (3) years or whenever a change in product formulation is made.

7 IDENTIFICATION OF CONTAINERS

Mark each container clearly and durably to show the following information:

- (a) name of manufacturer and/or supplier;
- (b) trade name of the product (if applicable);
- (c) product reference number or identification number;
- (d) grade(s) of polymer modified binder with which the precoating agent is compatible;
- (e) batch number or date of manufacture; and
- (f) "Use By" date.

Provide a copy of the certificate of compliance and Safety Data Sheet with each delivery.

8 INFORMATION TO BE PROVIDED BY SUPPLIER

Provide a Materials Data Sheet which includes the following information:

- (a) chemical and physical properties;
- (b) recommended application rate;
- (c) recommended diluent and rate of dilution, where applicable;
- (d) recommended method of mixing;
- (e) storage life of precoating agent before applying to aggregate, without precipitation or other deterioration;
- (f) effective life of precoating agent when applied to aggregate and stockpiled.

ANNEXURES 3268/A TO 3268/B – (NOT USED)

ANNEXURE 3268/C – SCHEDULE OF IDENTIFIED RECORDS

Refer to Clause 2.2.

The records listed below are Identified Records for the purposes of TfNSW D&C Q6 Annexure Q/E.

Clause	Description of Identified Record
5.7	Average and minimum value of concentration of active component and details of related tests.
6	Certificate of compliance verifying that the precoating agent complies with Clause 5 together with test results reported on NATA endorsed test documents.
7	Certificate of compliance and Safety Data Sheet to be supplied with each delivery.
8	Materials Data Sheet.

ANNEXURES 3268/D TO 3268/L – (NOT USED)

ANNEXURE 3268/M – REFERENCED DOCUMENTS

Refer to Clause 2.4.

TfNSW Specification

TfNSW D&C Q6 Quality Management System (Type 6)

TfNSW Test Methods

TfNSW T230 Resistance to Stripping of Cover Aggregates and Binders

TfNSW T238 Initial Adhesion of Cover Aggregates and Binders

TfNSW T590 Homogeneity of Precoats and Adhesion Agents

TfNSW Guides

TP-GDL-001 TfNSW Sprayed Sealing Guide

Australian Standards

AS 2157 Cutback Bitumen

AS/NZS ISO 9001 Quality management systems – Requirements

Austrroads Documents

AGPT04B/07 Guide to Pavement Technology - Part 4B: Asphalt