



**NOTES**

1. CONCRETE GRADE N25 AT 28 DAYS.
2. SIDE WALLS OF ALL PITS DEEPER THAN 1500 mm ARE TO BE REINFORCED WITH ONE LAYER OF SL82 MESH RETURNED 300 mm INTO BASE.
3. DEPTH OF PIT NOT TO EXCEED 3500 mm.
4. PITS DEEPER THAN 1200 mm TO BE FITTED WITH GALVANISED STEP IRONS.
5. ALL EXPOSED EDGES TO BE ROUNDED WITH 200 mm RADIUS.
6. MEDIAN WIDTH AS SHOWN IS FOR MINIMUM CONDITIONS.
7. ALL REINFORCEMENT LAPS 300 mm LONG.
8. FOR USE WITH FLEXIBLE PAVEMENT ONLY.

THIS DRAWING MAY BE PREPARED IN COLOUR AND MAY BE INCOMPLETE IF COPIED

50mm ON A3 SIZE ORIGINAL

QR CODE SCAN TO CHECK DOCUMENT VER.		REV	DATE	AMENDMENT / REVISION DESCRIPTION	WVR No.	APPROVAL	ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SHOWN	CONTACT DETAILS SEND FEEDBACK ON THIS STANDARD DRAWING TO : technologystandards@rms.nsw.gov.au	ISSUED SFR MANAGER ROAD POLICY, SPECIFICATIONS & TECHNOLOGY DATE 20.01.17	<b>Transport Roads &amp; Maritime Services</b>	<b>STANDARD DRAWING</b> ROAD DESIGN ENGINEERING R0220 STORMWATER DRAINAGE SERIES - GULLY PITS SLOTTED MEDIAN DRAINS SHEET 1 OF 1	STANDARD DRAWING No. <b>R0220-46</b> STATUS ISSUED EDMS No. DS2014/005867 ORIGINAL ISSUE DATE JANUARY 2017	REV. -
							SCALES ON A3 SIZE DRAWING		PREPARED BY ENGINEERING SERVICES ROAD POLICY, SPECIFICATIONS AND AND TECHNOLOGY				© Roads and Maritime Services