



Test method T235

Average least dimension of aggregate
(10 mm and greater)

OCTOBER 2012



Revision Summary

Ed/Rev Number	Clause Number	Description of Revision	Authorisation	Date
		Reformatted and Revision Summary Added	D Dash	May 1999
		Date on Test Method Revised to Agree with Date on Revision Summary	D Dash	Feb 2001
Ed 2/Rev 0	All	New Issue. Reference to AS 1141.20.1. Tolerance conforms.	J Friedrich	June 2010
Ed 3/ Rev 0	All	Reformatted RMS template	J Friedrich	October 2012

Note that Roads and Maritime Services is hereafter referred to as 'RMS'.

The most recent revision to Test method T235 (other than minor editorial changes) are indicated by a vertical line in the margin as shown here.

Test method T235

Average least dimension of aggregate (10 mm and greater)

1. Scope

This test method sets out the procedure for determining the average least dimension of aggregate particles of nominal size 10 mm and greater.

2. General

The test is applicable to aggregate particles with nominal size 10 mm and greater.

NOTE: Use T275 for aggregate particles with nominal size 5 mm or 7 mm.

3. Apparatus, Preparation, Procedure, Calculations and Reporting

- (a) For particles with nominal size 10 mm and greater use AS 1141.20.1 “Methods for sampling and testing aggregates – Average least dimension – Direct measurement (nominal size 10 mm and greater)” with the following amendments:
 - (i) Replace Clause 4(a) with
“Sieve the sample as outlined in AS 1141.11.1 or T201”.
 - (ii) In Clause 5.4 the slotted gauge method is the preferred method.
 - (iii) Include reference to this test method in the report.